


SOURCE: City of Farmington Hills GIS, 2013
Oakland County GIS, 2013

- All Weather Route
- Class A
- Class B
- Sections

TABLE OF MAXIMUM ALLOWABLE GROSS AXLE LOADINGS

Spacing Between Axles	Normal Loading When Restrictions Are Not in Force		Loadings When Restrictions Are in Force		
	Designated Class "A"	Normal Class "B"	Special Designated All Weather Routes	Designated Class "A"	Normal Class "B"
9 feet or over	S/A 18,000 lbs	S/A 18,000 lbs	S/A 20,000 lbs	S/A 13,500 lbs	S/A 11,700 lbs
More than 3 1/2 feet but less than 9 feet	T/A 13,000 lbs	T/A 13,000 lbs	T/A 17,000 lbs	T/A 9,750 lbs	8,450 lbs
When part of an tandem axle assembly	16,000 lbs	13,000 lbs	16,000 lbs	T/A 12,000 lbs	8,450 lbs
When less than 3 1/2 feet	9,000 lbs	9,000 lbs	9,000 lbs	6,750 lbs	5,850 lbs
Maximum load of any wheel shall not exceed lbs (per inch of tire width)	700 lbs	700 lbs	700 lbs	525 lbs	450 lbs



DISCLAIMER: Although the information provided by this map is believed to be reliable, its accuracy is not warranted in any way. The City of Farmington Hills assumes no liability for any claims arising from the use of this map.